

Garment finishing cabinet

FC4 8

Features and benefits

- Drying and finishing of all garments at low temperature
- Productivity of 70 items an hour for polyester-cotton 65/35 nurses overall
- Low installed power for energy savings
- Closed circuit running during part of the cycle for calorie recycling
- Fibres loosening by vaporisation of steam – integrated steam spray with built-in electric steam boiler
- Microprocessor controlled
- Right or left hand side control panel
- Door closing without locking, with security turning off heat and ventilation at opening
- Right or left hand side door hinges
- 18 kW electric, gas or steam heating
- Thermal insulation to save energy
- Programmable cool-down
- Access ramp for easy loading and unloading
- Two loading mobile trolleys with hangers

Main options

- Stainless steel panels
- Connection to an external steam network for vaporisation
- Kit of accessories
- Specific voltages (under request)



Main specifications	FC4 8		
Heating alternatives			
electric	kW	18	
gas	BTU/h (kW)	68290 (20)	
steam at 8-9 bar	kW	40	
Consumption data*	18kW	Gas	Steam
Total time full load	min	6	6
Energy consumption full load	kWh	2.7	0.22

Certified in accordance with ISO 9001 and ISO 14001.

Electrical connections			FC4 8
Heating	Voltage		
Electric	380-415V 3AC 50/60 Hz	kW(A)	13.6 (25) 19.6 (32)
Gas or Steam	380-415V 3AC 50/60 Hz 8-9 bar	kW(A)	1.6 (12)
Steam, gas and air connections			
Steam	DN		20
Steam pressure	kPa		600-1000
Steam consumption	kg/h		5
Condensate	DN		15
Gas	DN		20
Gas pressure			
	Natural gas	Pa	2000-2500
		mbar	20-25
	Propane gas	Pa	3700-5000
		mbar	37-50
Air outlet		ø mm	160
Evacuated air	electric	m ³ /h	525
	steam		525
	gas		360
Pressure drop (el./steam/gas)	Max. Pa		200/200/60
Sound levels			
Airborne sound level	dB(A)		<79
Shipping data (el./steam/gas)			
	net, kg		320/335/330
	crated, kg		450
Shipping volume	crated, m ³		3.53
Dimensions in mm			
A	Width		870
B	Depth		1300
C	Height		1975
D			1420
E			210
F			60
G			245
H			160
I			155
K			1000
L			435
M			1920
N			60
O			1350
1	Control panel	6	Water connection for built-in steam boiler
2	Exhaust connection	7	Drain for built-in steam boiler
3	Electrical connection	8	Gas inlet
4	Steam inlet	9	Main switch
5	Condensate return or gas inlet	10	External steam spray connection

