

Tensioning Form Finishers

FFT-D, FFT-WC



Features and benefits

- User-friendly control panel with display
- Pivoting control board
- Automatic finishing control with microprocessor for an elevated productivity
- 9 different work programmes for garments of any fabric and size
- Possibility to select ironing mode: automatic, semi-automatic or manual
- Rotating former (180° for FFT-D and 360° for FFT-WC) for an easy handiness of garments
- Vertical and horizontal garment tensioning for a perfect finish
- Removable front collar clamp
- Adjustable shoulders
- Automatic size adjustment
- Strong ventilation unit with air-regulation
- Possibility to exclude each of the tensioning devices according to needs
- Anti-stretching device
- Upgraded air heating system (for FFT-WC)

Main options

- 2HP motor
- All steam iron with support and teflon shoe (standard for FFT-WC)
- Clamps for side vents (standard for FFT-WC)
- 360° rotation of the form (for FFT-D)
- Side clamps
- Electronic air regulation (FFT-WC)
- Connection with steam trap for FFT-D without iron

Electrical connections		FFT-D	FFT-WC
Voltage			
400V 3N AC 50Hz	kW(A)	1.2(10)	1.2(10)
208-240V 3 AC 60Hz	kW(A)	1.2(10)	1.2(10)
Steam, air and vacuum connection			
Steam	DN	15	15
Rec. steam pressure	kPa	500-600	500-600
Steam consumption	kg/h	15-20	20-25
Condensate	DN	15	15
Compressed air	DN	8	8
Rec. air pressure	kPa	600-700	600-700
Air consumption	l/min	40	40
Shipping data			
	net, kg	160	170
	crated, kg	180	190
Dimensions in mm			
A Width		620	620
B Depth		1020	1020
C Height		1575-2325	1575-2325
D		780-1530	780-1530
E		550	550
F		345	345
G		795	795
H		1330	1330
I		830	830
J		530	530
K		160	160
L		40	40
M		45	45
<ol style="list-style-type: none"> 1 Control panel 2 Electrical connection 3 Steam inlet 4 Condensate 5 Air inlet 			

